



# TECHNICAL DATA SHEET

## BOSTON STRIP PARQUET OAK

*oiled / brushed / smoked*

### DIMENSIONS

• <b>Length:</b>	610 mm	610 mm
• <b>Width:</b>	122 mm	122 mm
• <b>Thickness:</b>	14 mm	15 mm

### PRODUCT COMPOSITION

- **Top layer:** approx. 3/4 mm real wood
- **Core:** 9 mm transverse poplar wood slats
- **Back veneer:** 2 mm longitudinal poplar wood veneer

*Slight bevel on long and short side*



### SURFACE FINISH

WOCA naturally oxidative hardened oil surface – ready for interior use. Suitable for residential and commercial areas with due regard to initial care and maintenance instructions recommended by the manufacturer. For use of a natural oil surface in commercial areas, special measures are necessary after consultation with the manufacturer.

### GLUE

Aica Aibon P-4405  
or equivalent

### CONNECTION

Traditional  
T/G connection

### COUNTRY OF ORIGIN

China

### PACKAGING

• <b>Pack:</b>	16 boards	8 left &	1,19 m <sup>2</sup>
• <b>Pallet:</b>	60 packs	8 right side	71,4 m <sup>2</sup>

### CERTIFICATION

E1 classified; fire class Dfl-s 1.

Suitable for warm water underfloor heating systems with due consideration of the standardized specifications. Suitable only for professional full surface glueing.