



TECHNICAL DATA SHEET

BOSTON 3-STRIP OAK

DIMENSIONS

- **Length:** 2200 mm
- **Width:** 189 mm
- **Thickness:** 14 mm

PRODUCT COMPOSITION

- **Top layer:** approx. 3 mm real wood
- **Core:** 9 mm transverse poplar wood slats
- **Back veneer:** 2 mm longitudinal poplar wood veneer



SURFACE FINISH

Either 6-times UV hardened acrylic matt lacquered (suitable only for residential areas) or WOCA naturally oxidative hardened oil surface – ready for interior use. Suitable for residential and commercial areas with due regard to initial care and maintenance instructions recommended by the manufacturer. For use on a natural oil surface in commercial areas, special measures are necessary after consultation with the manufacturer.

GLUE

AICA AIBON - 4405
or equivalent

CONNECTION

Uniclic® click system
on long and short side

COUNTRY OF ORIGIN

China

PACKAGING

- **Pack:** 8 boards 3,33 m²
- **Pallet:** 35 packs 133,20 m²

CERTIFICATION

E1 classified; fire class Dfl-s 1.

WOCA oil surface bears the IBR Seal of Approval for "recommended healthy living". Suitable for warm water underfloor heating systems with due consideration of the standardized specifications. Suitable for professional floating installation or full-surface bonding.