



TECHNICAL DATA SHEET

EURO 1-STRIP OAK

DIMENSIONS

- **Length:** 2.200 mm
- **Width:** 204 mm
- **Thickness:** 14 mm

PRODUCT COMPOSITION

- **Top layer:** approx. 4 mm real wood
- **Core:** 9 mm transverse spruce wood slats
- **Back veneer:** 2 mm longitudinal spruce wood veneer

Bevel on long side for oak, other wood sharp edge



SURFACE FINISH

Either 6-times UV hardened acrylic matt lacquered (suitable only for residential areas) or WOCA naturally oxidative hardened oil surface – ready for interior use. Suitable for residential and commercial areas with due regard to initial care and maintenance instructions recommended by the manufacturer. For use on a natural oil surface in commercial areas, special measures are necessary after consultation with the manufacturer.

GLUE

D3 Rakoll EBW 0301 (Fuller)
or equivalent

CONNECTION

Uniclic® click system
on long side

COUNTRY OF ORIGIN

EU

PACKAGING

- **Pack:** 8 boards 3,59 m²
- **Pallet:** 40 packs 125,65 m²

CERTIFICATION

E1 classified; fire class Dfl-s 1.

Suitable for warm water underfloor heating systems with due consideration of the standardized specifications. Suitable for professional floating installation or full-surface bonding. Please observe and follow the installation (laying) instructions.