



# TECHNICAL DATA SHEET

## EURO 1-STRIP OAK XL

### DIMENSIONS

- **Length:** 2,200 mm
- **Width:** 249 mm
- **Thickness:** 15 mm

### PRODUCT COMPOSITION

- **Top layer:** approx. 4 mm real wood
- **Core:** 9 mm transverse spruce wood slats
- **Back veneer:** 2 mm longitudinal spruce wood veneer  
*Bevel lengthwise*



### SURFACE FINISH

WOCA naturally oxidative hardened oil surface – ready for interior use. With due regard to initial care and maintenance instructions recommended by the manufacturers, suitable for residential and commercial areas. For use in commercial areas, special measures are necessary after consultation with the manufacturer.

### GLUE

D3 Rakoll EBW 0301 (Fuller)  
or equivalent

### CONNECTION

Uniclic® click system  
on long side

### COUNTRY OF ORIGIN

EU

### PACKAGING

- |                  |          |                       |
|------------------|----------|-----------------------|
| • <b>Pack:</b>   | 8 boards | 3,29 m <sup>2</sup>   |
| • <b>Pallet:</b> | 32 packs | 105.28 m <sup>2</sup> |

### CERTIFICATION

E1 classified; fire class Dfl-s 1.  
WOCA oil surface bears the IBR Seal of Approval for "recommended healthy living". Suitable for warm water (except Oak antique smoked white oiled) underfloor heating systems with due consideration of the standardized specifications. Suitable for professional floating installation or fullsurface bonding. Please observe and follow the installation (laying) instructions.