



# TECHNICAL DATA SHEET

## BOSTON STRIP PARQUET OAK

*oiled / brushed/ smoked*

### DIMENSIONS

- **Length:** 610 mm
- **Width:** 122 mm
- **Thickness:** 14 mm

### PRODUCT COMPOSITION

- **Top layer:** approx. 3 mm real wood
- **Core:** 9 mm transverse poplar wood slats
- **Back veneer:** 2 mm longitudinal poplar wood veneer

*Slight bevel on long and short side*



### SURFACE FINISH

WOCA naturally oxidative hardened oil surface – ready for interior use. Suitable for residential and commercial areas with due regard to initial care and maintenance instructions recommended by the manufacturer. For use of a natural oil surface in commercial areas, special measures are necessary after consultation with the manufacturer.

### GLUE

Prefere 4405  
by dynea or equivalent

### CONNECTION

Traditional  
T/G connection

### COUNTRY OF ORIGIN

China

### PACKAGING

- |                  |           |                      |                     |
|------------------|-----------|----------------------|---------------------|
| • <b>Pack:</b>   | 16 boards | 8 left, 8 right side | 1,19 m <sup>2</sup> |
| • <b>Pallet:</b> | 60 packs  |                      | 71,4 m <sup>2</sup> |

### CERTIFICATION

E1 classified; fire class Dfl-s 1.

WOCA oil surface bears the IBR Seal of Approval for "recommended healthy living". Suitable for warm water underfloor heating systems with due consideration of the standardized specifications. Suitable only for professional full surface glueing.