



Thede & Witte
FERTIGPARKETT

Technical data sheet

T&W Boston 1-strip XL wide board Modul

Dimensions

Length: 2200 mm
Width: 260 mm
Thickness 15 mm

Product composition

Top layer: approx. 4 mm real wood*
Core: 9 mm transverse poplar wood slats
Back veneer: 2 mm longitudinal poplar wood veneer



Slight bevel on long side

**(2 longitudinal slats with different fixed widths. Wide slats with a transverse joint, narrow slats with two transverse joints)*

Surface finish

Woca naturally oxidative hardened oil surface – ready for interior use.
With due regard to initial care and maintenance instructions recommended by the manufacturers, suitable for residential and commercial areas.
For use in commercial areas, special measures are necessary after consultation with the manufacturer.

Glue

Prefere 4405 by dynea or equivalent

Connection

Uniclic® click system on long side

Country of origin

China

Packaging

6 boards per pack: 3.43 m²
40 packs per pallet: 137.20 m²

Certification

E1 classified; fire class Dfl-s 1.
Woca oil surface bears the IBR Seal of Approval for “recommended healthy living”.
Suitable for warm water underfloor heating systems with due consideration of the standardized specifications. Suitable for professional floating installation or full-surface bonding.
Please observe and follow the installation (laying) instructions.

As per: January 2017. Subject to change without prior notice