



Thede & Witte
FERTIGPARKETT

Technical data sheet

T&W Boston 1-strip antique

Dimensions

Length:	1860 mm	1900 mm
Width:	189 mm	189 mm
Thickness:	15 mm	15 mm

Product composition

Top layer:	approx. 4 mm real wood	
Core:	9 mm transverse poplar wood slats	
Back veneer:	2 mm longitudinal poplar wood veneer	



Slight bevel on long side and short side

Surface finish

Woca naturally oxidative hardened oil surface – ready for interior use.
With due regard to initial care and maintenance instructions recommended by the manufacturers, suitable for residential and commercial areas.
For use in commercial areas, special measures are necessary after consultation with the manufacturer.

Glue

Prefere 4405 by dynea or equivalent

Connection

Uniclic® click system on long and short side

Country of origin

China

Packaging

8 boards per pack:	2.81 m ²	2,87 m ²
40 packs per pallet:	112.40 m ²	114,80 m ²

Certification

E1 classified; fire class Dfl-s 1.

Woca oil surface bears the IBR Seal of Approval for "recommended healthy living".

Suitable for warm water (*except Oak antique smoked white oiled*) underfloor heating systems with due consideration of the standardized specifications. Suitable for professional floating installation or full-surface bonding.

Please observe and follow the installation (laying) instructions.

As per: January 2018. Subject to change without prior notice