



**Thede & Witte**  
FERTIGPARKETT

# Technical data sheet

T&W Boston 3-strip – matt lacquered/oiled/brushed/ smoked

## Dimensions

Length: 2200 mm  
Width: 189 mm  
Thickness 14 mm

## Product composition

Top layer: approx. 3 mm real wood  
Core: 9 mm transverse poplar wood slats  
Back veneer: 2 mm longitudinal poplar wood veneer

## Surface finish

Either 6-times UV hardened acrylic matt lacquered (suitable for residential areas) or naturally oxidative hardened oil surface – ready for interior use.  
Suitable for residential and commercial areas with due regard to initial care and maintenance instructions recommended by the manufacturer.  
For use on a natural oil surface in commercial areas, special measures are necessary after consultation with the manufacturer.

## Glue

Preferre 4405 by dynea or equivalent

## Connection

Uniclic® click system on long and short side

## Country of origin

China

## Packaging

8 boards per pack: 3.33 m<sup>2</sup>  
40 packs per pallet: 133.20 m<sup>2</sup>

## Certification

E1 classified; fire class Dfl-s 1.  
Woca oil surface bears the IBR Seal of Approval for “recommended healthy living”.  
Suitable for warm water underfloor heating systems with due consideration of the standardized specifications. Suitable for professional floating installation or full-surface bonding.  
Please observe and follow the installation (laying) instructions.

As per: April 2018. Subject to change without prior notice