



**Thede & Witte**  
FERTIGPARKETT

# Technical data sheet

T&W Euro 1-strip – coniferous wood, matt lacquered/oiled

## Dimensions

Length: 2000 mm  
Width: 161 mm  
Thickness: 15 mm

## Product composition

Top layer: approx. 3.5 mm real wood  
Core: 9 mm transverse solid wooden core  
Back veneer: 2 mm longitudinal spruce wood veneer



Bevel on long side

## Surface finish

Either 6-times UV hardened acrylic matt lacquered (suitable for residential areas) or naturally oxidative hardened oil surface – ready for interior use.  
Suitable for residential and commercial areas with due regard to initial care and maintenance instructions recommended by the manufacturer.  
For use on a natural oil surface in commercial areas, special measures are necessary after consultation with the manufacturer.

## Glue

D3 Rakoll EBW 0301 (Fuller) or equivalent

## Connection

Loc-it (5G-s) connection

## Country of origin

EU

## Packaging

8 boards per pack: 2.25 m<sup>2</sup>  
42 packs per pallet: 94.50 m<sup>2</sup>

## Certification

E1 classified; fire class Dfl-s 1.  
Suitable for warm water underfloor heating systems with due consideration of the standardized specifications. Suitable for professional floating installation or full-surface bonding.  
Please observe and follow the installation (laying) instructions.

As per: January 2017. Subject to change without prior notice